No.F.19-11/2022-IS-6

Government of India
Ministry of Education
Department of School Education & Literacy
(IS-6 Section)

Shastri Bhawan, New Delhi Dated 30th September, 2022

To

The Pr. Secretaries/ Secretaries (School Education) of all States/UTs.

Sub: Accelerating the Setting up of Vidya Sameeksha Kendras in all the States and UTs – Reg.

Sir / Madam,

NEP2020 caters to a multitude of requirements along with many schemes run by the Ministry of Education that benefit different facets of education & stakeholders. But running multiple schemes brings in challenges in effective implementation due to lack of:

- a. Visibility to stakeholders 'Ability to See' what's going on in almost real time
- b. Insights about what's happening 'Ability to Make Sense' of what's working/what's not
- c. Coordination in driving improvements 'Ability to Amplify Actions' through timely, coordinated efforts based on data & insights.

The ability to effectively collect, monitor, correlate, and analyse data will lead to timely actions to implement schemes. Various initiatives of the Ministry of Education like UDISE, NAS, NIPUN BARAT, DIKSHA etc. are efficient systems working in silos. Integrating various data sets and breaking through the barrier of operating in silos will help us effectively leverage different entities towards a common goal.

Vidya Samiksha Kendra (VSK) is aimed at leveraging data and technology to bring a bid leap in learning outcomes. This will cover data of more than 15 Lakh schools, 96 Lakh teachers and 26 Crore students and analyse them meaningfully using big data analysis, artificial intelligence and machine learning in order to enhance the overall monitoring of the education system and there by improving learning outcomes.

For setting up Vidya Sameeksha Kendras in all the States and UTs, the following budget has been approved during the year 2022-23:

(Rs. In Crore)

Model	No. of		Unit Cos	t per State	/UT	Total Amount			
and Range of Schools	States and UTs	States/ UTs	Non- Recurring	Recurring	Total	Non- Recurring	Recurring	Total	
Model I (<1000 Schools)	5	Andaman & Nicobar Islands, Chandigarh, Daman & Diu & Dadra & Nagar Haveli, Lakshadweep, Puducherry,	1.7	0.3	2.0	8.5	1.5	10.0	
Model II (>1000 and ≤5000)	8	Arunachal Pradesh, Goa, Ladakh, Manipur, Mizoram, Nagaland, Sikkim, Tripura	2.5	0.5	3.0	20.0	4.0	24.0	
Model III (>5000 and ≤30,000)	6	Delhi, Haryana, Jammu & Kashmir, Meghalaya, Punjab, Uttarakhand	3.2	0.8	4.0	19.2	4.8	24.0	
Model IV (>30,000)	10	Andhra Pradesh, Assam, Bihar, Chhattisgarh, Jharkhand, Karnataka, Tamil Nadu, Telangana, Uttar Pradesh, West Bengal	4.2	0.9	5.0	41.5	8.5	50.0	
		Total				89.2	18.8	108.0	

Already Central VSK has been established at CIET, NCERT and starter pack for States / UTs is also developed by CIET, NCET for helping the States and UTs to get their VSK going. For any assistance regarding the Starter Pack and for any technical issues CIET, NCERT can be consulted by all the States and UTs.

In order to accelerate the setting up of the VSKs, a roadmap has been prepared only as an illustration. Suggested Video Wall solutions have also been worked out and the Specs / cost is also shared only as an illustration and not as a norm and States / UTs are having total flexibility in setting up the VSK and States / UTs are encouraged to be innovative in setting up the VSK.

This is issued with the approval of competent authority.

Encl: As above

(Dr. E. Naveen Nicolas)

Director

Ph: 011-23384325 naveen.nicolas@nic.in

Copy to:-

- The Commissioner / Director / State Project Directors of Samagra Siksha of all the States and UTs
- 2. JD, CIET, NCERT, New Delhi.

ROADMAP FOR ACCELERATING THE SETTING UP OF VSK (ONLY FOR ILLUSTRATION)

Phase	Typical Duration	Key Outputs
Phase 1:	1 month	Appointment of Nodal officer
Getting Started		Leverage the starter pack shared by NCERT and NIC to get the VSK going quickly. Participate in workshops with NCERT-NIC to demystify NDEAR compliant VSK and understand how to go about it.
Phase 2: Defining and Planning	1 month	Identify Key Programs and key metrics against which State / UT would like to drive actions and improve them.
		Define contours for physical Infrastructure and hardware that will enable the VSK.
		Establish the specifications for hardware and software keeping NDEAR compliance in purview
		Identify the skill sets and experience needed to manage & run the VSK
Phase 3: Engaging	1 month	Set up the relevant teams on the program, data, hardware, software side.
		Create a plan with them to enable them to take the right actions.
Phase 4: Go LIVE	1-2	Deploy physical & digital infra like Video Wall, Hardware, Software etc.
	months	2. Deploy the team to run campaigns
Phase 5: Roll Out	1 month	Initiate the pilot to run campaigns by taking requisite actions using emitted data.
		Set up mechanisms to distribute data across locations and stakeholders to enable localised and targeted actions as per the insights.
Phase 6: Expand	1-3 months	Expand the distribution of analytical insights to different stakeholders at different levels
		Configure more programs, datasets & campaigns.
		Can further enhance the software and hardware capabilities to meet the needs.

VIDEO WALL SOLUTIONS (ONLY FOR ILLUSTRATION)

SI.No	Details	Cost (In Lakhs)	Remarks
	Video wall solution – 1 (2X2 display)	Rs. 41.15	Details enclosed in Annexure – III
2	Video wall solution – 2 (3X3 display)	Rs. 65.22	Details enclosed in Annexure – IV
3	Video wall solution – 3 (136 Inch display)	Rs. 95.42	Details enclosed in Annexure – V

Annexuse- III

Draft No. DFA/3565035

Attachment:2X2 Videowall, pdf

_:							
	Videpwall Solution						
S.	Description		25			reaction (See).	
<u>.</u>	2X2 Display 0.88 Bezel,atawali Display full HD .500 nits,Contrast Ration 1100:1.Colour Depth 1.07 10 Bit rate,response 8 mil,Lan port in and Out.DP in and out put port,2 HDMI port.		1	Nos. '	1650000	1650000	
2	Wall Management software for 24/7 Running Critical applications Command and Control Software Graphical user and interface user friendly User Interface Software and Programming, Select the logic symbols the system will require, assign signals to those symbols, and connect the signals to other symbols or devices as determined by the program Software shoule be able to provide custom layouts for BMS Systems, Access Control, LCTV Monitoring, Fire Alarm, HVAC with annotation on Sources.		1	Nos.	235000	235000	
3	10.1 Touch Panel for AV Controlling stylish and versatile wall mount touch screen featuring web browsing with Built- in Software Videowall, custom-programmable Icons, H.265/H.264 streaming video, Wifi Network, POE 400 Nits, Contrast ratio 1000:1, Aspect Ratio 16:10, viewing angle ±80° horizontal & ±80° verdical, 5-point Multitouch, Voice Recognition, Ram 26B, 100 Mbps, auto switching, auto negodating, auto discovery & Goud management.		1	Nos.	135000	135000 "	
i L	Switcher for Multiple Input and Out Connectivity 8 Port in and Out, Handles HDMI devices with Deep Color, 3D, 4K, and high-bitrate 7.1 encoded audio, Snables high-performance H.264 streaming from any Input source up to 1080p, HDCP 2.2 Compilant, Modular Inputs support a complete range of digital, analog, and streaming signal types, Web Browsed Controller Support 4K@60 4:44, USB IIID extention for a local keyboard/mouse or computer, AV signal format management.			Nos.	950000	950000	
3	Room Controller and AV Swiething 2 Gb Ram and 8GB Flash Memory, Supports 50 and SDHC cards up to 32 GB and USB storage Support 1 TB, (Phone, IPad, and Androld device control app support, computer and web based control, Onboard IR/serial, COM, I/O, relay, IPv6 Reday, Bacnet Support, Built in SNMP V3 Support Etc., Active Directory service authentication, controllable thru FC, 1000 Mbps, auto-switching, auto-negotiating, auto-discovery & Cloud management.		1	Nas.	150000	150000 ,. • .]
6	AV Network Switch 24 Port With 10G ModualPre-configured for Out-of-Box L2 Multicast (SDVoE-ready)Prevent petwork flooding with effortless multicast implementation of Layer 2 Multicast		1 .	Nos.	225000	-225000	
7.	Wireless Datasharing Solution HDMI Input for direct connection of a mini-PC or other local source, or portable laptop computer via an optional wall plate or cable. The HDMI Input supports HD 1080p signals, HDCP 1.4 compilant input a output device central via CEC, IK, or RS-232, compatible with iOS, Androld, Windows, macOS, Chroma OŞ etc., miracast support. PuE Powered & Clayd management.	1	. 1	Nos	175000	175000	
В	AOC HDMI 18 GHZ Cable 15 Meter		В	Nos.	29500	236000	
2	Network Access Paint Dual band Wifi 6		1	Nos,	22000	22000	1
10	Server rack 42 U 1200X1200	1	1	Nos.	52000	52000.	1
<u> [[</u>	Sound Mixer and 2.1 Speaker		1	Nos.	135000	135000	1
12	Installtion and Translog		1	Nos.	150000	- 150000]
	Total					4115000	ŀ
			1				

					-	
	Videowall Solution		in in Kal			- 1 L
Sr.	Description		Qty.	Quit	Omerice Oppr	Adiquin Lift No.
1	3X3 Display 1.8 Bezel, atawali Display full HD .500 nits, Contrast Ration 1100:1. Colour Depth 1.07 10 Bit rate, response 8 mil, Lan port in and Out, DP in and out put port, 2 HDMI port.	1 - 1 1 1	1	Nos.	2950000	2950000
2	Wall Management software for 24/7 Running Critical applications. Command and Control. Software Graphical user and Interface user friendly User Interface. Software and Programming. Select the logic symbols the system will require, assign signals to those symbols, and connect the signals to other symbols or devices as determined by the program .Software shoule be able to provide custom layouts for BMS Systems, Access Control, CCTV Monitoring, Fire Alarm, HVAC with anotation on Sources.		1	Nas.	235000	235000
3	10.1 Touch Panel for AV Controlling stylish and versatile wall mount touch screen featuring web browsing with Built- in Software Videowall, custom-programmable icons, H.265/H.264 streaming video, Wifi Network, POE 400 Nits, Contrast ratio 1000:1, Aspect Ratio 16:10, viewing angle ±80° horizontal & ±80° vertical; 5-point Multitouch, Voice Recognition, Ram 2GB, 100 Mbps, auto switching, auto negotiating, auto discovery & Cloud management.		1	Nos.	135000	135000
	Matrix Chasis Based Switcher for Multiple Input and Out Connectivity 16 Portin and Out, Handles HDMI devices with Deep Color, 3D, 4K, and high-bitrate 7.1 encoded audio Enables high-performance H.264 streaming from any input source up to 1080p, HDCP 2.2 Compliant, Modular inputs support a complete range of digital, analog, and streaming signal types, Web Browsed Controller Support 4K@60 4:4:4, USB HID extention for a local keyboard/mouse or computer, AV signal format management via EDID & Cloud management.	-	1	Nos.	1650000	1650000
;	Room Controller and AV Swicthing 2 Gb Ram and 8GB Flash Memory, Supports SD and SDHC cards up to 32 GB and USB storage Support I TB, iPhone, iPad, and Android device control app support, computer and web based control, Onboard IR/serial, COM, I/O, rolay, IPv6 Reday, Bacnet Support, Built in SNMP V3 Support Etc., Active Directory service authentication, controllable thru PC, 1000 Mbps, auto-switching, auto-negotiating, auto-discovery & Cloud changement.	, 	1	Nos.	150000	150000
5	AV Network Switch 24 Port With 10G ModualPre-configured for Out-of-Box 1.2 Multicast (SDVoE-ready)Prevent notwork flooding with effortless multicast implementation of Layer 2 Multicast		1	Nas.	225000	225000
· - [Wireless Datasharing Solution HDMI input for direct connection of a mini-PC or other local source, or portable laptop computer via an optional wall plate or cable. The HDMI input supports HD 1080p signals, HDCP 1.4 compliant input & output, device control via CEC, IR, or RS-232, compatible with iOS, Android, Windows, macOS, Chrome OS etc., miracast support, PoE Powered & Cloud management.	-	1	Nos.	175000	175000
<u>:</u>	AOC HDMI 18 GHZ Cable 15 Meter		15	Nos.	29500	442500
	Network Access Point Dual band Wifi 6		1	Nos,	22000	22000
	Server rack 42 U 1200X1200		1	Nos.	52000	52000
	Sound Mixer and 2.1 Speaker				135000	135000
2	installtion and Traning Total		1	Nos.	350000 ·	350000
- 1						

Annexue- I

1146

7 ~	ᆣ.						
	-	Videowall Solution	Yara.	i k	ing affire		
Ş		Description 126 beautiful 127	了"这 [4]	Oty	Link	Unit Phie	Amatine (prec)
1		136 Inch LED Zero Bezel, Datawall Display full HD	*****	1 7	Nos.	6500000	6500000
~	-	Data Wall Processor with require input and Out put	_	1	Nos.	1550000	1550000
3		Wall Management software for 24/7 Running Critical applications Command and Control Software Graphical user and Interface user friendly User Interface Software and Programming. Select the logic symbols the system will require, assign signals to those symbols, and connect the signals to other symbols or devices as determined by the program. Software shoule be able to provide custom layouts for BMS Systems, Access Control, CCTV Monitoring, Fire Alarm, HVAC with annotation on Sources.		1	Nos.	435000	435000
4	1	10.1 Touch Panel for AV Controlling stylish and versatile wall mount touch screen featuring web browsing with Built-in Software Videowall, custom-programmable icons, H.265/H.264 streaming video, Wifi Network, POE 400-Nits, Contrast ratio 1000:1, Aspect Ratio 16:10, viewing angle ±80° horizontal & ±80° vertical, 5-point Multitouch, Voice Recognition, Ram 2GB, 100 Mbps, auto switching, auto negotiating, auto discovery & Cloud management.		1	Nos.	135000	135000
5		Room Controller and AV Swicthing 2 Gb Ram and 8GB Flash Memory, Supports SD and SDHC cards up to 32 GB and USB storage Support 1 TB, iPhone, iPad, and Android device control app support, computer and web based control, Onboard IR/serial, COM, I/O, relay, IPv6 Reday, Bacnet Support, Built in SNMP V3 Support Etc., Active Directory service authentication, controllable thru PC, 1000 Mbps, auto-switching, auto-negotiating, auto-discovery & Cloud management.	_	1	Nos.	150000	1500,00
13		AV Network Switch 24 Port With 10G ModualPre-configured for Out-of-Box L2 Multicast (SDVoE-ready)Prevent in two flooding with effortless multicast implementation of Layer 2 Multicast		.1	Nos.	225000	.225000
	Ü	Wireless Datasharing Solution HDMI input for direct connection of a mini-PC or other local source, or portable laptop computer via an optional wall plate or cable. The HDMI input supports HD 1080p signals, HDCP 1.4 compliant Input & output, degice control via CEC, IR, or RS-232, compatible with iOS, Android, Windows, macOS, Chrome OS etc., miracast support, PoE Powered & Cloud management.		1	Nos.	175000	175000
	1	OC HOMI 18 GHZ Cable 15 Mêter		5	Nos.	29500	147500
	: 12	e wer rack 42 U 1260X1200		1	Nos.	22000	22000
1		nstalltion and Transing		_	Nos.	52000	5202C
۳,	+::	againent and righting			Nos.	150000	150600
ļ	+	Total					9541509